Bamboo Panel Coloring Guide

This guide describes the recommended procedure for changing the color of OOTOUCH bamboo panels using Bona® Primers. The information below is provided for guidance only and does not constitute a guarantee of the final color.

1. Surface preparation

- Sand the raw panel evenly (120–150 grit).
- Carefully remove all dust.
- The panel must be clean and dry.

2. Primer application

- Apply the Bona Primer using a microfibre roller.
- The number of coats applied affects the color intensity. One or two coats may be applied depending on the desired appearance. It is the applicator's responsibility to adjust the number of coats to achieve the desired final color.
- Follow Bona's recommended drying times.

3. Finishing lacquer

- Apply 2 coats of Bona Traffic HD lacquer.
- Choose the desired finish: Extra Matt, Satin or Gloss.

Recommendations

- Always carry out a trial before production.
- The number of coats affects the color intensity.
- As bamboo is a natural material, each panel has its own unique shade variations.

ootouch©
DECO-RESPONSIBLE SOLUTIONS

Finish correspondence

The OOTOUCH finish names below correspond to the recommended Bona Primers.

OOTOUCH PANEL Intemporel	OOTOUCH PANEL Classic	Primer Bona	Final Color
Champagne	Caramel	White	Light Champagne
Champagne	Caramel	Natural	Intense Champagne
Champagne	Caramel	Classic UX	GOLD
Champagne	Caramel	Classic	GOLD
Caramel 1 triangle	Caramel	Intense	CAMEL / CARAMEL
Caramel 2 triangles	Caramel	Amber	CARAMEL

Important

The finishes above indicate the recommended coloring system. The final appearance depends on the natural characteristics of the bamboo, surface preparation, application conditions, the number of coats and the lacquer used. Colors cannot therefore be considered contractual color references.

Always carry out a trial first.

Bamboo is a natural material; color variations are normal.

The final appearance depends on sanding, application conditions and the number of primer coats.

The final lacquer will not change the color; it provides the final surface protection.

Si c'est pour compléter un chantier de parquet, le préciser à la commande.

Pour toute validation esthétique, OOTOUCH recommande l'utilisation d'échantillons réels et la réalisation d'un essai avant la mise en production.