Bona Cleaner

WOOD FLOOR CLEANER

Concentrated detergent for cleaning of finished wood and cork floors.



Bona Cleaner is a highly concentrated, slightly alkaline cleaner specifically designed for the cleaning of finished wood and cork floors. Bona Cleaner can be used for regular mopping or in a machine-based cleaning program.

- Specifically designed for lacquered wood and cork floors
- Efficient, low-foaming formula
- Leaves no dulling residue
- For daily maintenance and regular cleaning

TECHNICAL DATA

pH-value:	Concentrate ca. 11
Base:	Solution of synthetic soaps
Dilution:	Normal cleaning: 0.5 dl to 5 liters of water (1%) Heavily soiled floors: 1 dl to 5 liters of water (2%)
Application tools:	Bona Cleaning Pad, cotton cloth, cleaning mop
Shelf life:	At least 2 years, from the date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	3 x 5 liters (44 boxes per pallet) 10 x 1 liters (50 boxes per pallet)

Additional detailed information is noted in the appropriate Safety Data Sheet.

Bona Cleaner

WOOD FLOOR CLEANER

Concentrated detergent for cleaning of finished wood and cork floors.

PREPARATIONS

Remove loose dust/grit etc. using a vacuum cleaner, scissor mop or other dry-cleaning method.

APPLICATION

Dilute concentrate according to recommendation and clean the floor using a mop or an auto scrubber equipped with a white or tan pad. Note that excessive use of water may damage the floor. Always keep the amount of water used to clean to a minimum and be careful where the floor has open gaps. Replace the cleaning water periodically to avoid streaking.

AUTO SCRUBBER

Recommendations for use of auto scrubber:

1. Always fill the tank with clean water prior to use.
2. Run the machine along, never across, the parquet boards.
3. Water loss from the machine must not exceed 1 lit/100 m². Test by adding 10 liters of water to the tank and check the remaining water after 100 m² (e.g. 5 x 20 m). 9 liters should remain in the tank.
4. Water should be removed promptly, make sure not to leave puddles when turning with the machine.
5. If distributing water with the machine, the water must be removed within 3 minutes.
6. Keep the rubber band clean and in good trim. Replace annually or if the machine is leaving puddles or too much water.
7. Do not use aggressive pads on the surface. Aggressive pads may scratch and wear on the surface. The milder the pad, the lesser the wear.

Bona Polish (matt & gloss)

WOOD FLOOR MAINTEANCE

Waterborne coating for frequent maintenance



Bona Polish (Gloss & Matt) is a ready-to-use maintenance coating designed for lacquered wood flooring but with the flexibility of being possible to use on a variety of flooring types. Polish fills up micro scratches and produces a sacrificial wear layer that protects the original surface. Bona Polish is reinforced with polyurethane for increased resistance to wear and is suitable for both domestic and commercial environments.

- Possible to use on a variety of floors including varnished floors, laminate, linoleum,
- PVC and ceramic tiles.
- Reinforced with polyurethane for increased durability.
- Excellent flow for a flawless surface
- Meets EN 14904:2006 (only gloss version)

TECHNICAL DATA

Product base:	Waterborne acrylate & polyurethane mix dispersion
Sheen:	Gloss, matt
Dilution:	Do not dilute, product is ready-to-use
Drying time:	~1 hour (20°C/60% RH)
Application tools:	Bona Applicator Pad
Coverage:	~ 50 m²/liter
Cleaning:	Clean tools in soap and water. Dried stains can be removed with Bona Remover or acetone
Shelf life:	Gloss: 2 years, from date of production, in unopened original container Matt: 1 year, from date of production, in unopened original container.
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.

Bona Polish (matt & gloss)

WOOD FLOOR MAINTEANCE

Waterborne coating for frequent maintenance

Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	10 x 1 liter (50 boxes per pallet 3 x 5 liters (44 boxes per pallet)

Additional detailed information is noted in the appropriate Safety Data Sheet.

PREPARATION

Remove loose dirt and grit from your floor. Depending on the degree of soiling, mix a suitable solution of Bona Cleaner or Bona Deep Clean Solution and wet clean the floor thoroughly. Observe that any remaining dirt will become trapped in the coating and cannot be removed afterwards. Let floor dry completely.

Do not use Bona Polish on any floor that has been waxed or oiled as residues from these materials may disrupt the adhesion to the surface. It is recommended to always test the adhesion to the surface and check for desired results prior to using Bona Polish.

APPLICATION

1. Shake container thoroughly before use. Apply polish in a 3-4 cm wide wavy line on a 3 m² section of the floor and without delay, spread the product using a flat polish application pad. For best results, maintain a thin consistent coat.
2. Without adding more product, smooth out the section by moving the applicator with the grain of the wood.
3. Continue with next section and then allow the ready treated floor minimum 1 hour drying time before resuming light foot traffic on the floor. If needed, a second coat of polish can be applied after 2 hours.

Avoid heavy traffic and the replacement of furniture and rugs until next day. To achieve a uniform aspect, it is advised to always treat the entire surface.

MAINTENANCE

Wet cleaning of the floor may be carried out after three days drying. For regular cleaning use Bona Cleaner. Do not use strongly alkaline cleaning agents as they may damage the floor or remove the protective coating of polish.

TIPS

- When smoothing out the product, keep the applicator pad flat to the surface and apply from wall-to-wall. Avoid lifting the applicator along the way as this produces bubbles.

Bona Polish (matt & gloss)

WOOD FLOOR MAINTEANCE

Waterborne coating for frequent maintenance

- Do not work into areas starting to dry as this may produce streaking.
- If applying multiple layers of polish, do not stress the drying time between coats. Risk of dissolving previous layers.