REF: F13BCNA142

BambooTouch® by ootouch

STYLE INTEMPOREL BAMWOOD®/ **Massif** [Nairobi]

Our floors from the Intemporel Bamwood® range are made from bamboo strips assembled under very high pressure, giving them a noble, elegant look. The slats are factory-finished, either with a matt UV varnish or with a matt Woca® oil. Beyond being beautiful, Intemporel Bamwood® is exceptionally hard and resistant (wear, indentation...). Several installation types are available for all uses. Most can be used in wet rooms as well as with underfloor heating. The quality of our products allows us to offer a warranty of up to 30 years, provided that installation is carried out in compliance with the standards in force in the country (and by following our maintenance recommendations).

Glued
YES
Floating
NO
Underfloor heating
YES
Bathroom*
YES



GENERAL DATA ON THE PRODUCT STRUCTURE

Finish: Varnished or oiled
Dimensions: 13 x 142 x 1850mm
Wear layer: +/- 4mm
Underlay: No
Structure: Solid
Bevel: GO2
Interlocking*: Groove / Tongue
Box content: 2,1m² / 25,5 kg

TECHNICAL DATA

Brinell hardness: ± 9 kg/mm² (EN 1534)
Contraction coefficient: 0.14% per % of moisture variation
Moisture content: 10% at 20°C and 65% relative humidity
8% at 20°C and 50% relative humidity
Density: ± 1.050 kg/m³
Fire rating: CFL-S1 or BFL-S1 if glued
Formaldehyde emissions: E0, <0,008mg/m²h (EN 717-2 CTIB DE670X417 and EN 16000-9)
PCP content: below the detection limit (CTIB 5229/2)
VOC Free: below the detection limit (EN15052 CTIB 5229/2)
Thermal conductivity: λ=±0,24W/mK

STORAGE, INSTALLATION REQUIREMENTS AND MAINTENANCE (DTU 51.2 standard or local standard, depending on installation type)

- The slats must be stored flat at a temperature of 15 to 25° and a relative humidity of 45 to 65%.
- The floor requires acclimatization and must be left for 48h in its packaging at the installation site.
- Bamboo is a natural product. Variations in shade, tone, grain or gloss are normal. Be sure to mix the slats from the different packs before installation. Any installed floor will be considered accepted.
- The screed must be dry, clean and even. Comply with the standards in force regarding moisture content, evenness and permissible load. Residual moisture must not exceed 2.7%.
- Allow an expansion gap of +/- 1cm all around the floor and obstacles.
- Provide an expansion joint every 8 to 10m.
- Checking and raised fibres may occur on oiled finishes. This phenomenon is natural and does not give rise to a warranty claim. Light sanding followed by oiling will reduce it.
- Blanchon® oil is not compatible with our oiled floors.
- Installation, cleaning and maintenance instructions are available (see our website ootouch.be)

* Installation over underfloor heating must be glued. A floating installation creates an insulating air layer that slightly reduces underfloor heating performance. Installation in a bathroom must be glued (except for the Ecootouch range). The perimeter sealing must be carried out very carefully. For a floating installation, the grooves and tongues must be glued, and a vapour barrier installed.

WARRANTY: up to 30 years subject to conditions - See our website ootouch.eu

nv ootouch sa
Av du Commerce 33 - 1420 Braine-l'Alleud • Belgium | Tel. : +32 (0)2 384 58 77 | **info@ootouch.be** | **ootouch.eu**